


一厘太
はじめました



タップ オーバーサイズ

+0.1 +0.2 +0.3 +0.6

- ◎ 溶融亜鉛メッキ(どぶ付けメッキ)の加工物に最適です
- ◎ 材質は高バナジウムハイス鋼で耐摩耗性に優れています
- ◎ 一般鋼、低中炭素鋼、合金鋼などに / 手回し加工・機械加工用



HSSハンドタップ オーバーサイズ +0.2												
呼び	食付	品番	食付	品番	形状 Type	形状寸法					溝数	価格
						L	ℓ	d	K	kℓ		
M6X1.0	中(#2)	HHO060M2+0.2	上(#3)	HHO060M3+0.2	A	61	24	6	4.5	7	3	1,780
M8X1.25	中(#2)	HHO080N2+0.2	上(#3)	HHO080N3+0.2	C	70	30	6.2	5	8	4	2,660
M10X1.5	中(#2)	HHO100O2+0.2	上(#3)	HHO100O3+0.2	C	75	32	7	5.5	8	4	3,380
M12X1.75	中(#2)	HHO120P2+0.2	上(#3)	HHO120P3+0.2	C	82	38	8.5	6.5	9	4	4,720
M16X2.0	中(#2)	HHO160Q2+0.2	上(#3)	HHO160Q3+0.2	C	95	45	12.5	10	13	4	8,620

HSSハンドタップ オーバーサイズ +0.3												
呼び	食付	品番	食付	品番	形状 Type	形状寸法					溝数	価格
						L	ℓ	d	K	kℓ		
M8X1.25	中(#2)	HHO080N2+0.3	上(#3)	HHO080N3+0.3	C	70	30	6.2	5	8	4	2,660
M10X1.5	中(#2)	HHO100O2+0.3	上(#3)	HHO100O3+0.3	C	75	32	7	5.5	8	4	3,380
M12X1.75	中(#2)	HHO120P2+0.3	上(#3)	HHO120P3+0.3	C	82	38	8.5	6.5	9	4	4,720
M16X2.0	中(#2)	HHO160Q2+0.3	上(#3)	HHO160Q3+0.3	C	95	45	12.5	10	13	4	8,620
M20X2.5	中(#2)	HHO200R2+0.3	上(#3)	HHO200R3+0.3	C	105	50	15	12	15	4	15,390

HSSハンドタップ オーバーサイズ +0.6												
呼び	食付	品番	食付	品番	形状 Type	形状寸法					溝数	価格
						L	ℓ	d	K	kℓ		
M12X1.75	中(#2)	HHO120P2+0.6	上(#3)	HHO120P3+0.6	C	82	38	8.5	6.5	9	4	5,050
M16X2.0	中(#2)	HHO160Q2+0.6	上(#3)	HHO160Q3+0.6	C	95	45	12.5	10	13	4	9,240
M20X2.5	中(#2)	HHO200R2+0.6	上(#3)	HHO200R3+0.6	C	105	50	15	12	15	4	16,480

HSSスパイラルタップ オーバーサイズ +0.1												
呼び	品番	形状 Type	精度	形状寸法							溝数	価格
				L	ℓ	d	Ln	Dn	K	kℓ		
M6X1.0	HSO060M+0.1	B	+0.1	61	19	6	27	4.8	4.5	7	3	2,100
M8X1.25	HSO080N+0.1	D	+0.1	70	22	6.2	30	5.9	5	8	3	3,050
M10X1.5	HSO100O+0.1	D	+0.1	75	24	7	34	6.7	5.5	8	3	3,860
M12X1.75	HSO120P+0.1	D	+0.1	82	29	8.5	41	8.2	6.5	9	3	5,380
M14X2.0	HSO140Q+0.1	D	+0.1	88	30	10.5	44	10.1	8	11	3	7,370
M16X2.0	HSO160Q+0.1	D	+0.1	95	32	12.5	47	12.1	10	13	3	9,770
M18X2.5	HSO180R+0.1	D	+0.1	100	37	14	52	13.5	11	14	3	13,440
M20X2.5	HSO200R+0.1	D	+0.1	105	37	15	54	14.5	12	15	3	17,440

HSSスパイラルタップ オーバーサイズ +0.2												
呼び	品番	形状 Type	精度	形状寸法							溝数	価格
				L	ℓ	d	Ln	Dn	K	kℓ		
M8X1.25	HSO080N+0.2	D	+0.2	70	22	6.2	30	5.9	5	8	3	3,050
M10X1.5	HSO100O+0.2	D	+0.2	75	24	7	34	6.7	5.5	8	3	3,860
M12X1.75	HSO120P+0.2	D	+0.2	82	29	8.5	41	8.2	6.5	9	3	5,380
M14X2.0	HSO140Q+0.2	D	+0.2	88	30	10.5	44	10.1	8	11	3	7,370
M16X2.0	HSO160Q+0.2	D	+0.2	95	32	12.5	47	12.1	10	13	3	9,770
M18X2.5	HSO180R+0.2	D	+0.2	100	37	14	52	13.5	11	14	3	13,440
M20X2.5	HSO200R+0.2	D	+0.2	105	37	15	54	14.5	12	15	3	17,440
M22X2.5	HSO220R+0.2	D	+0.2	115	38	17	55	16.5	13	16	4	22,460
M24X3.0	HSO240S+0.2	D	+0.2	120	45	19	62	18.5	15	18	4	28,180